

IDEA

/CROLL COLGANTE (05.AA36.2010.__ / 05.AA36.2112.__ / 05.AA36.2210.__)



Light Output Ratio:	74.0%
Luminaire Power:	11.49 W

SHR Nominal:	0.00	Calculated using the TM5
SHR Maximum:	1.00	fine grid method.

C Range: 0 - 360DEG
C Interval: 30.0DEG
Test Speed: HIGH
Temperature: 25.3DEG

Test Date: 2021-07-22

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System: EVERFINE GO-2000B_V1 SYSTEM V2.00.421
Humidity: 65.0%
Test Distance: 10.000m [K=1.0000]
Remarks:


/CROLL COLGANTE (05.AA36.2010.__ / 05.AA36.2112.__ / 05.AA36.2210.__)

LUMINAIRE PHOTOMETRIC TEST REPORT


Test:U:230.13V I:0.0529A P:11.492W PF:0.9435 Freq:49.99Hz Lamp Flux:1190.07x1 lm		
NAME: CROLL COLGANTE	TYPE:LED	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:200697
MFR.:	SUR.:	Shielding Angle:

DATA OF LAMP		PHOTOMETRIC DATA				Eff: 76.67 lm/W
MODEL	CXB1512-27G-M2-NOU	I _{max} (cd)	4518	S/MH(C0/180)	0.37	
NOMINAL POWER(W)	12	LOR(%)	74.0	S/MH(C90/270)	0.35	
RATED VOLTAGE(V)	230	TOTAL FLUX(lm)	881.17	η _{UP,DN} (C0-180)	0.0,37.8	
NOMINAL FLUX(lm)	1190.07	CIE CLASS	DIRECT	η _{UP,DN} (C180-360)	0.0,36.3	
LAMPS INSIDE	1	η _{up} (%)	0.0	CIBSE SHR NOM	0.00	
TEST VOLTAGE(V)	230	η _{down} (%)	74.0	CIBSE SHR MAX	1.00	

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



C0 PLANE ISOLUX DIAGRAM (UNIT:lx)



C Range: 0 - 360DEG
 C Interval: 30.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Test Date:2021-07-22

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-2000B_V1 SYSTEM V2.00.421
 Humidity:65.0%
 Test Distance:10.000m [K=1.0000]
 Remarks:




IDEA

/CROLL COLGANTE (05.AA36.2010.__ / 05.AA36.2112.__ / 05.AA36.2210.__)

LUMINANCE LIMITATION CURVES

Test:U:230.13V I:0.0529A P:11.492W PF:0.9435 Freq:49.99Hz Lamp Flux:1190.07x1 lm		
NAME: CROLL COLGANTE	TYPE:LED	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:200697
MFR.:	SUR.:	Shielding Angle:



C Range: 0 - 360DEG
C Interval: 30.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Test Date:2021-07-22


γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.00.421
Humidity:65.0%
Test Distance:10.000m [K=1.0000]
Remarks:

/CROLL COLGANTE (05.AA36.2010.__ / 05.AA36.2112.__ / 05.AA36.2210.__)

CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

Test:U:230.13V I:0.0529A P:11.492W PF:0.9435 Freq:49.99Hz Lamp Flux:1190.07x1 lm		
NAME: CROLL COLGANTE	TYPE:LED	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:200697
MFR.:	SUR.:	Shielding Angle:

ρ_{cc}	80%			70%			50%			30%			10%			0
ρ_w	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
ρ_c	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio			Coefficients of Utilization(CU)												
0.0	.88	.88	.88	.86	.86	.86	.82	.82	.82	.79	.79	.79	.76	.76	.76	.74
1.0	.83	.82	.81	.82	.81	.79	.79	.78	.77	.76	.75	.75	.74	.73	.73	.71
2.0	.79	.77	.75	.78	.76	.74	.76	.74	.73	.74	.72	.71	.72	.71	.70	.69
3.0	.76	.73	.71	.75	.72	.70	.73	.71	.69	.71	.70	.68	.70	.68	.67	.66
4.0	.73	.70	.67	.72	.69	.67	.70	.68	.66	.69	.67	.66	.68	.66	.65	.64
5.0	.70	.67	.64	.69	.66	.64	.68	.66	.64	.67	.65	.63	.66	.64	.63	.62
6.0	.67	.64	.62	.67	.64	.62	.66	.63	.61	.65	.63	.61	.64	.62	.61	.60
7.0	.65	.62	.60	.65	.62	.60	.64	.61	.59	.63	.61	.59	.62	.60	.59	.58
8.0	.63	.60	.58	.63	.60	.58	.62	.59	.57	.61	.59	.57	.61	.59	.57	.56
9.0	.61	.58	.56	.61	.58	.56	.60	.58	.56	.60	.57	.55	.59	.57	.55	.55
10.0	.59	.56	.54	.59	.56	.54	.59	.56	.54	.58	.56	.54	.58	.55	.54	.53



C Range: 0 - 360DEG
C Interval: 30.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Test Date:2021-07-22

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.00.421
Humidity:65.0%
Test Distance:10.000m [K=1.0000]
Remarks:

/CROLL COLGANTE (05.AA36.2010.__ / 05.AA36.2112.__ / 05.AA36.2210.__)

UGR(Unified Glare Rating) Table

Test:U:230.13V I:0.0529A P:11.492W PF:0.9435 Freq:49.99Hz Lamp Flux:1190.07x1 lm											
NAME: CROLL COLGANTE					TYPE:LED			WEIGHT:			
SPEC.:					DIM.:			SERIAL No.:200697			
MFR.:					SUR.:			Shielding Angle:			
ceiling/cavity		0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
walls		0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
working plane		0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions		Viewed crosswise					Viewed endwise				
x = 2H	y = 2H	15.8	16.5	16.0	16.6	16.8	15.9	16.6	16.1	16.8	16.9
	3H	15.7	16.3	15.9	16.5	16.7	15.8	16.4	16.0	16.6	16.8
	4H	15.6	16.2	15.8	16.4	16.6	15.7	16.3	16.0	16.5	16.7
	6H	15.5	16.1	15.8	16.3	16.5	15.6	16.2	15.9	16.4	16.7
	8H	15.5	16.0	15.8	16.2	16.5	15.6	16.1	15.9	16.4	16.6
	12H	15.4	15.9	15.7	16.2	16.5	15.5	16.1	15.8	16.3	16.6
4H	2H	15.6	16.2	15.9	16.4	16.6	15.7	16.3	16.0	16.5	16.8
	3H	15.5	16.0	15.8	16.2	16.5	15.6	16.1	15.9	16.4	16.6
	4H	15.4	15.8	15.7	16.1	16.4	15.5	16.0	15.8	16.2	16.5
	6H	15.3	15.7	15.6	16.0	16.3	15.4	15.8	15.7	16.1	16.5
	8H	15.2	15.6	15.6	15.9	16.3	15.3	15.7	15.7	16.1	16.4
	12H	15.1	15.5	15.6	15.9	16.3	15.3	15.6	15.7	16.0	16.4
8H	4H	15.2	15.6	15.6	15.9	16.3	15.3	15.7	15.7	16.1	16.4
	6H	15.1	15.4	15.5	15.8	16.2	15.2	15.5	15.6	15.9	16.3
	8H	15.0	15.3	15.5	15.7	16.2	15.1	15.4	15.6	15.8	16.3
	12H	15.0	15.2	15.4	15.7	16.1	15.1	15.3	15.5	15.8	16.2
12H	4H	15.1	15.5	15.6	15.9	16.3	15.3	15.6	15.7	16.0	16.4
	6H	15.0	15.3	15.5	15.7	16.2	15.1	15.4	15.6	15.8	16.3
	8H	15.0	15.2	15.4	15.7	16.1	15.1	15.3	15.5	15.8	16.2
Variations with the observer position at spacings:											
S = 1.0H		+ 2.6 / - 8.0					+ 2.7 / - 7.8				
1.5H		+ 4.5 / - 5.5					+ 4.5 / - 5.3				
2.0H		+ 5.3 / - 9.3					+ 5.6 / -10.0				

CIE Pub.117, 1190 lm Total Lamp Luminous Flux Correct (8log(F/F0) = 0.6)
Area: 0.001 m2


C Range: 0 - 360DEG
C Interval: 30.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Test Date:2021-07-22

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.00.421
Humidity:65.0%
Test Distance:10.000m [K=1.0000]
Remarks:

/CROLL COLGANTE (05.AA36.2010.__ / 05.AA36.2112.__ / 05.AA36.2210.__)

AAI Figure

Test:U:230.13V I:0.0529A P:11.492W PF:0.9435 Freq:49.99Hz Lamp Flux:1190.07x1 lm		
NAME: CROLL COLGANTE	TYPE:LED	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:200697
MFR.:	SUR.:	Shielding Angle:



Note:The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG
C Interval: 30.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Test Date:2021-07-22

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.00.421
Humidity:65.0%
Test Distance:10.000m [K=1.0000]
Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

Test:U:230.13V I:0.0529A P:11.492W PF:0.9435 Freq:49.99Hz Lamp Flux:1190.07x1 lm		
NAME: CROLL COLGANTE	TYPE:LED	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:200697
MFR.:	SUR.:	Shielding Angle:

Table-1

UNIT: cd

[illegible]

C Range: 0 - 360DEG
C Interval: 30.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Test Date:2021-07-22

γRange: 0 - 90DEG
 γInterval: 1.0DEG
 Test System:EVERFINE GO-2000B_V1 SYSTEM V2.00.421
 Humidity:65.0%
 Test Distance:10.000m [K=1.0000]
 Remarks: